

## My Spot Ø25 Long Surface

Designed by FLOS Architectural, 2024



LED - Power LED - 4W - 203lm - 2700K - CRI> 90 - Beam° 11

LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling             |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 4                   |
| Source flux (lm)       | 271                 |
| Lumen Output (lm)      | 203                 |

### Physical

|                          |               |
|--------------------------|---------------|
| Colour                   | Brushed Steel |
| Rotation (°)             | 360           |
| Longitudinal tilting (°) | 90            |
| Net weight (kg)          | 0.52          |
| IP internal              | 20            |
| IP external              | 20            |

### Download

Mounting instructions  PDF

### Photometric Files

LDT / IES  ZIP

### Technical Drawings

2D  ZIP

2D  ZIP

3D  ZIP

3D  ZIP


### Ecodesign and Energy Labelling



Non-replaceable light source



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 11        |
| Beam angle C90-270 (°) | 11        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                     |              |
|---------------------|--------------|
| Insulation class    | I            |
| Main voltage (Vac)  | 220          |
| Forward voltage (V) | 3            |
| LED current (mA)    | 800          |
| Power supply        | Integrated   |
| Dimmable            | No           |
| Power supply type   | Non Dimmable |
| Batteries inside    | No           |