

My Spot Ø25 Long Surface

Designed by FLOS Architectural, 2024



LED - Power LED - 4.7W - 199lm - 3000K - CRI> 90 - Beam° 34

LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling             |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 4.7                 |
| Source flux (lm)       | 326                 |
| Lumen Output (lm)      | 199                 |

### Physical

|                          |       |
|--------------------------|-------|
| Colour                   | Black |
| Rotation (°)             | 360   |
| Longitudinal tilting (°) | 90    |
| Net weight (kg)          | 0.52  |
| IP internal              | 20    |
| IP external              | 20    |

Download

Mounting instructions

ZIP

Photometric Files

LDT / IES

ZIP

Technical Drawings

2D

ZIP

2D

ZIP

3D

ZIP

3D

ZIP


Ecodesign and Energy Labelling

LED

Non-replaceable light source



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 34        |
| Beam angle C90-270 (°) | 34        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | I                                     |
| Main voltage (Vac)  | 220                                   |
| Forward voltage (V) | 3                                     |
| LED current (mA)    | 800                                   |
| Power supply        | Integrated                            |
| Dimmable            | Yes                                   |
| Power supply type   | Dimmable Casambi                      |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |
| Batteries inside    | No                                    |