

My Spot Ø25 Short Surface

Designed by FLOS Architectural, 2024



LED - Power LED - 4W - 187lm - 2700K - CRI> 90 - Beam° 34

LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	4
Source flux (lm)	271
Lumen Output (lm)	187

Physical

Colour	Brushed Bronze
Rotation (°)	360
Longitudinal tilting (°)	90
Net weight (kg)	0.5
IP internal	20
IP external	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings


- 2D  ZIP
- 2D  ZIP
- 3D  ZIP
- 3D  ZIP

Ecodesign and Energy Labelling

  Non-replaceable light source



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	34
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	I
Main voltage (Vac)	220
Forward voltage (V)	3
LED current (mA)	800
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No