

My Spot Ø35 Long Casambi

Designed by FLOS Architectural, 2024

LED - LED array - 8.2W - 641lm - 2700K - CRI> 90 - Beam° 32



LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	8.2
System power (W)	11.4
Source flux (lm)	756
System flux (lm)	641

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20



Download

- Family spec sheet
- ↓ ZIP
- Mounting instructions
- ↓ PDF

Photometric Files


- LDT / IES
- ↓ ZIP

Technical Drawings

- 2D
- ↓ ZIP
- 3D
- ↓ ZIP



Schematic light drawing



Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	90
Rg gamut index	100
LED Life / Failure Ratio	L70B50>45.000h_Tc85°C
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	600
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No