

My Spot Ø35 Short Casambi

Designed by FLOS Architectural, 2024



LED - LED array - 11W - 580lm - 2700K - CRI> 90 - Beam° 15

LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	11
System power (W)	12.1
Source flux (lm)	756
System flux (lm)	580

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings


2D	ZIP
3D	ZIP




Schematic light drawing



Ecodesign and Energy Labelling



Non-replaceable light source



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	90
Rg gamut index	100
LED Life / Failure Ratio	L70B50>45.000h_Tc85°C
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	570
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No