

My Spot Ø35 Short Non Dimmable

Designed by FLOS Architectural, 2024




LED - LED array - 11W - 641lm - 2700K - CRI> 90 - Beam° 32

LED lighting module for installation in the Zero Track Pro. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the track connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	11
System power (W)	11.4
Source flux (lm)	756
System flux (lm)	641

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20

Download

- Family spec sheet

ZIP
- Mounting instructions

PDF

Photometric Files

- LDT / IES

ZIP

Technical Drawings


- 2D

ZIP
- 3D

ZIP




Schematic light drawing



Ecodesign and Energy Labelling



Non-replaceable light source



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	90
Rg gamut index	100
LED Life / Failure Ratio	L70B50>45.000h_Tc85°C
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	Yes
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	700
Driver	Remote
Dimmable	No
Dimming type	Non Dimmable
Batteries inside	No