

## My Spot Ø35 Short Surface

Designed by FLOS Architectural, 2024




LED - LED array - 9.4W - 556lm - 3000K - CRI> 90 - Beam° 15

LED lighting module for surface-mounted applications. Optical with double focal lens technology, low glare and high visual comfort. Adjustable by tilting and turning. In the downlight position, the connector arm is perfectly flush with the product.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                   |           |
|-------------------|-----------|
| Mounting          | Ceiling   |
| LED type          | LED array |
| Lamp category     | LED       |
| Number of lamps   | 1         |
| Power (W)         | 9.4       |
| System power (W)  | 11.5      |
| Source flux (lm)  | 711       |
| Lumen Output (lm) | 556       |

### Physical

|                          |                |
|--------------------------|----------------|
| Colour                   | Brushed Bronze |
| Rotation (°)             | 360            |
| Longitudinal tilting (°) | 90             |
| Net weight (kg)          | 0.67           |
| IP internal              | 20             |
| IP external              | 20             |

### Download

Mounting instructions [Download PDF](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)




### Ecodesign and Energy Labelling

 Non-replaceable light source

 Replaceable control gear by a professional

Schematic light drawing



Photometric

|                          |                       |
|--------------------------|-----------------------|
| Lighting type            | Direct                |
| Light distribution       | Symmetric             |
| CCT (K)                  | 3000                  |
| CRI>                     | 90                    |
| McAdam steps (SDCM)      | 2                     |
| Rf fidelity index        | 90                    |
| Rg gamut index           | 100                   |
| LED Life / Failure Ratio | L90B50>50.000h_Tc85°C |
| Beam angle C0-180 (°)    | 15                    |
| Beam angle C90-270 (°)   | 15                    |
| Extreme cut off          | No                    |
| UGR <sub>L</sub>         | <10                   |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | I               |
| Frequency (Hz)      | 50/60           |
| Main voltage (Vac)  | 220             |
| Forward voltage (V) | 18              |
| LED current (mA)    | 400             |
| Power supply        | Integrated      |
| Dimmable            | Yes             |
| Power supply type   | Dimmable DALI 2 |
| Batteries inside    | No              |