

FLOS

03.2211.14A Black

Nano Spot

Designed by FLOS Architectural, 2020



LED - Power LED - 2W - 70lm - 3000K - CRI> 90 - Beam° 23

Accent lighting LED module to be installed in The Micro Running Magnet System.
Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	2
System power (W)	2
Source flux (lm)	170
System flux (lm)	70
Efficacy (lm/W)	43.75

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Length (in)	1.62
Net weight (lb)	6.999999999999999E-2
Gross weight (lb)	0.2
IP internal	20



Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)
3D [ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23
UGR _L	<19

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)