

# FLOS

03.2213.40A White

## Nano Spot

Designed by FLOS Architectural, 2020



LED - Power LED - 2W - 82lm - 5000K - CRI> 90 - Beam° 23

Accent lighting LED module to be installed in The Micro Running Magnet System.  
Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 2                   |
| System power (W)       | 2                   |
| Source flux (lm)       | 200                 |
| System flux (lm)       | 82                  |
| Efficacy (lm/W)        | 51.25               |

### Physical

|                          |                      |
|--------------------------|----------------------|
| Color                    | White                |
| Orientation              | Adjustable           |
| Rotation (°)             | 267                  |
| Longitudinal tilting (°) | 90                   |
| Length (in)              | 1.62                 |
| Net weight (lb)          | 6.999999999999999E-2 |
| Gross weight (lb)        | 0.2                  |
| IP internal              | 20                   |



### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |


### Photometric Files

|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |


### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by a  
professional



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 5000      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 23        |
| Beam angle C90-270 (°) | 23        |
| UGR <sub>L</sub>       | <19       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| Driver              | Remote excluded                       |
| Dimmable            | Yes                                   |
| Dimming type        | Non Dimmable, Dimmable                |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |