

Nano Spot Adressable

Designed by FLOS Architectural, 2026



LED - Power LED - 2W - 70lm - 3000K - CRI> 90 - Beam° 23

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic converter. "Addressable" version, with individual control of up to 3 addresses or groups.

 Drawing Thumbnail

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	2
System power (W)	2
Source flux (lm)	170
Lumen Output (lm)	70
Efficacy (lm/W)	43.75

Physical

Colour	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Spot diameter (mm)	13
Length (mm)	41
Net weight (kg)	0.03
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)


3D [Download ZIP](#)

Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	23
Beam angle C90-270 (°)	23
Extreme cut off	No
UGR _L	<19

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)