

FLOS

03.2217.40A White

Nano Spot Non Dimmable

Designed by FLOS Architectural, 2020



LED - Power LED - 2W - 86lm - 4000K - CRI> 90 - Beam° 32

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic current converter. On/Off version, non-dimmable.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	2
System power (W)	2
Source flux (lm)	185
System flux (lm)	86
Efficacy (lm/W)	53.75

Physical

Color	White
Orientation	Adjustable
Rotation (°)	267
Length (in)	1.62
Net weight (lb)	6.9999999999999993E-2
Gross weight (lb)	0.2
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	---------------------


Technical Drawings

2D	ZIP
3D	ZIP

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	32
Beam angle C90-270 (°)	32
Extreme cut off	No
UGRL	<16

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)