

# FLOS

09.8302.AH Glossy Grey


## Oblique

Designed by Vincent Van Duysen, 2020

LED - Top LED - 7W - 525lm - 4000K - CRI> 90 - Beam° 35

Table lamp emitting asymmetrical direct light through a patented ultra-flat lens. Die-cast aluminium body with USB-C port and On/off switch located on the base. Integrated timer system. Available in a Qi wireless charging option integrated into the base.

Designed by Vincent Van Duysen to revolutionise desk lighting, Oblique is a true hybrid of design and productivity. The natural evolution of the classic articulated desk lamp, it redefines modern task lighting with its ultra-precise beam, excellent visual comfort and clean minimal form. As advanced as it is discreet, the lamp integrates a USB-C port and wireless charging function that offers charging while freeing desks from unsightly wires.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Table               |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 7                   |
| System power (W)       | 16.5                |
| Source flux (lm)       | 827                 |
| System flux (lm)       | 525                 |

### Physical

|             |             |
|-------------|-------------|
| Color       | Glossy Grey |
| Orientation | Fixed       |
| IP internal | 20          |
| IP external | 20          |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Asymmetric                    |
| CCT (K)                  | 4000                          |
| CRI>                     | 90                            |
| LED Life / Failure Ratio | L90B10 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 35                            |
| Beam angle C90-270 (°)   | 46                            |
| Extreme cut off          | No                            |

Electrical

|                           |                 |
|---------------------------|-----------------|
| Insulation class          | III             |
| Main voltage (Vac)        | 110-240         |
| Driver                    | Remote included |
| Dimmable                  | Yes             |
| Dimming type              | Dimmable        |
| Emergency type            | No              |
| Induction recharge QI     | No              |
| Charging socket/connector | USB-C           |