

## Oblique Floor


Designed by Vincent Van Duysen

LED - Top LED - 7W - 482lm - 3000K - CRI> 90 - Beam° 34



Floor lamp emitting asymmetrical direct light through a patented ultra-flat lens. Die-cast aluminium body. On/off switch sensor and dimmer function located on the head.

Designed by Vincent Van Duysen, Oblique Floor extends the Oblique philosophy into lounge and reading spaces. With its calculated height and angled beam, it delivers exceptional visual comfort and minimal aesthetics. Ideal for task lighting beside reading chairs or in professional settings, it combines performance and discretion. A hybrid of design and productivity, dimmer functionality and a charging port make it the ideal companion.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Floor               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Top LED             |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 7                   |
| System power (W)       | 10                  |
| Lumen Output (lm)      | 482                 |

### Physical

|                     |             |
|---------------------|-------------|
| Colour              | Matte White |
| Length (mm)         | 200         |
| Cord length (mm)    | 2500        |
| Net weight (kg)     | 3.32        |
| Package height (mm) | 120         |
| Package width (mm)  | 30          |
| Package length (mm) | 30          |
| IP internal         | 20          |

Download

Mounting instructions PDF

Photometric Files

LDT / IES ZIP

Technical Drawings


2D ZIP

3D ZIP

Bim ZIP



Schematic light drawing



Ecodesign and Energy  
Labelling

Replaceable (LED only)  
light source by a  
professional

Replaceable control  
gear by an end-user

Photometric

|                          |                            |
|--------------------------|----------------------------|
| Lighting type            | Direct                     |
| Light distribution       | Asymmetric                 |
| CCT (K)                  | 3000                       |
| CRI>                     | 90                         |
| McAdam steps (SDCM)      | 3                          |
| LED Life / Failure Ratio | L90B10 > 50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 34                         |
| Beam angle C90-270 (°)   | 46                         |
| Extreme cut off          | No                         |

Electrical

|                     |                 |
|---------------------|-----------------|
| Frequency (Hz)      | 50/60           |
| Main voltage (Vac)  | 110-240         |
| Forward voltage (V) | 24              |
| Power supply        | Remote included |
| Dimmable            | Yes             |
| Power supply type   | Dimmer on board |
| Dimming range (%)   | 1-100           |
| Precabled           | Yes             |
| Plug type           | Twist and Lock  |