

Oblique Floor


Designed by Vincent Van Duysen

LED - Top LED - 7W - 482lm - 3000K - CRI> 90 - Beam° 34



Floor lamp emitting asymmetrical direct light through a patented ultra-flat lens. Die-cast aluminium body. On/off switch sensor and dimmer function located on the head.

Designed by Vincent Van Duysen, Oblique Floor extends the Oblique philosophy into lounge and reading spaces. With its calculated height and angled beam, it delivers exceptional visual comfort and minimal aesthetics. Ideal for task lighting beside reading chairs or in professional settings, it combines performance and discretion. A hybrid of design and productivity, dimmer functionality and a charging port make it the ideal companion.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Floor
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	7
System power (W)	10
System flux (lm)	482

Physical

Color	Matte White
IP internal	20

Download

Mounting instructions



Photometric Files

LDT / IES



Technical Drawings


2D




3D



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	46
Extreme cut off	No

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	24
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Dimming range (%)	1-100
Precabled	Yes
Plug type	Twist and Lock