

FLOS

09.8231.DX Matte Rust


Oblique Floor USB-C

Designed by Vincent Van Duysen

LED - Top LED - 7W - 482lm - 3000K - CRI> 90 - Beam° 34

Floor lamp emitting asymmetrical direct lighting through a patented ultra-flat lens. Die-cast aluminium body with a USB-C port integrated into the base. On/off switch sensor and dimmer function located on the head.

Designed by Vincent Van Duysen, Oblique Floor extends the Oblique philosophy into lounge and reading spaces. With its calculated height and angled beam, it delivers exceptional visual comfort and minimal aesthetics. Ideal for task lighting beside reading chairs or in professional settings, it combines performance and discretion. A hybrid of design and productivity, dimmer functionality and a charging port make it the ideal companion.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Floor
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	7
System power (W)	16.5
Lumen Output (lm)	482

Physical

Colour	Matte Rust
Length (mm)	200
Cord length (mm)	2500
Net weight (kg)	3.32
Package height (mm)	120
Package width (mm)	30
Package length (mm)	30
IP internal	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by an end-user

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	34
Beam angle C90-270 (°)	46
Extreme cut off	No

Electrical

Frequency (Hz)	50/60
Main voltage (Vac)	110-240
Forward voltage (V)	24
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmer on board
Dimming range (%)	1-100
Precabled	Yes
Plug type	Twist and Lock
Charging socket/connector	USB-C