FLOS

09.8311.DR Matte Anthracite

Oblique Qi

Designed by Vincent Van Duysen, 2020

LED - Top LED - 7W - 482lm - 3000K - CRI> 90 - Beam° 35

Table lamp emitting asymmetrical direct light through a patented ultra-flat lens. Die-cast aluminium body with USB-C port and On/off switch located on the base. Integrated timer system.Available in a Qi wireless charging option integrated into the base.

Designed by Vincent Van Duysen to revolutionise desk lighting, Oblique is a true hybrid of design and productivity. The natural evolution of the classic articulated desk lamp, it redefines modern task lighting with its ultra-precise beam, excellent visual comfort and clean minimal form. As advanced as it is discreet, the lamp integrates a USB-C port and wireless charging function that offers charging while freeing desks from unsightly wires.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Table
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	7
System power (W)	26.5
Source flux (lm)	760
Lumen Output (lm)	482

Physical

Colour	Matte Anthracite
Orientation	Fixed
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions PDF

Photometric Files

LDT / IES ZIP

Technical Drawings

2D ZIP

3D ZIP

Bim ZIP

©2026 Flos - P.IVA 00290820174 - 8/6/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

RG
IEC 62471

GWT 850°

IP 20

Schematic light drawing



Luminous flux luminaire
482 lm

Beam Angle: 35°

h(m)	E(lx)	D(m)
1	231	2.18
2	58	4.36
3	26	6.54
4	14	8.72
5	9	10.90

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46
Extreme cut off	No

Electrical

Insulation class	III
Main voltage (Vac)	110-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable
Emergency	No
Induction recharge QI	Yes
Charging socket/connector	USB-C

©2026 Flos - P.IVA 00290820174 - 8/6/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.