

## Outgraze 50 Easy L 600 mm Non Dimmable Deep Brown

Designed by FLOS Outdoor, 2019



Integrated 220/240V power supply. Installation brackets, to be ordered separately.  
Sandblasted glass.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793361918 |
| Mounting               | Wall          |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Top LED       |
| Number of lamps        | 1             |
| Power (W)              | 15            |
| System power (W)       | 14.5          |
| Lumen Output (lm)      | 620           |

### Physical

|                         |            |
|-------------------------|------------|
| Colour                  | Deep Brown |
| Trim                    | No         |
| Orientation             | Adjustable |
| Transversal tilting (°) | 180        |
| Length (mm)             | 600        |
| Net weight (kg)         | 1.9        |
| Package height (mm)     | 970        |
| Package width (mm)      | 120        |
| Package length (mm)     | 120        |
| Package volume (m3)     | 0.01       |
| IP internal             | 66         |
| Drive Over              | No         |



### Download

Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)

### Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

[Bim](#) [ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 90        |
| Beam angle C90-270 (°) | 90        |

Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply

|                                                                                            |                                                                                                    |                                                                                                       |                                                                                                         |
|--------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
|           |                   |                     |                      |
| REQUIRED<br>Accessory<br>F021Z010000<br>Plug&play connector 4 poles                        | REQUIRED<br>Accessory<br>F021Z030000<br>4-pole plug&play connector + 3-pole cable, 5000 mm length. | REQUIRED<br>Accessory<br>F990C00A000<br>2 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable) | REQUIRED<br>Accessory<br>F990C010000<br>3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable) |
|          |                 |                    |                                                                                                         |
| REQUIRED<br>Accessory<br>F990C080000<br>Connector kit 5-pole flying socket + EU plug IP68. | REQUIRED<br>Accessory<br>F1204018<br>One pair of long brackets L 200 mm. Deep Brown                | REQUIRED<br>Accessory<br>F1203018<br>One pair of short brackets L 80 mm. Deep Brown                   |                                                                                                         |