

# FLOS


FA52502301.A White

## Perseo 1

Designed by FLOS Outdoor, 2012



LED source included. Integrated electrical power supply 100-240V ON- OFF. Fixing bracket included. Equipped with a 700 mm protruding section of neoprene cable and a kit with crimpable connectors and adhesive heat-shrinkable sleeves that guarantee the tightness of the connection. Optional accessories: ground spike; feet for ground mounting and arms for wall mounting (IP68 connector included). Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793641447 |
| Mounting               | Wall, Ground  |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| System power (W)       | 7             |
| Source flux (lm)       | 428           |
| Lumen Output (lm)      | 357           |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | White      |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 200        |
| Net weight (kg)          | 0.61       |
| Package height (mm)      | 85         |
| Package width (mm)       | 145        |
| Package length (mm)      | 235        |
| IP internal              | 65         |

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



## Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 40        |
| Beam angle C90-270 (°) | 40        |
| Extreme cut off        | No        |

## Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | II           |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 100-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

## Accessories & Power Supply



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)



OPTIONAL  
Accessory

FA136

Ground Spike Aimer 1/Aimer  
2/Aimer 3/Perseo 2



OPTIONAL  
Accessory

FA15801

Wall Bracket/Pole 600 mm Perseo  
1



OPTIONAL  
Accessory

FA15701

Wall Bracket/Pole 300 mm Perseo  
1