

FLOS


FA52507330-310 Black

Perseo 3 Street Optic Dimmable 1-10V

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Fixing bracket included. Equipped with a M16x1.5 cable guide (for 4.5mm<ø<10mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793642956
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	20
Source flux (lm)	2424
Lumen Output (lm)	1080

Physical

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	146
Net weight (kg)	2.28
Package height (mm)	135
Package width (mm)	190
Package length (mm)	315
Package volume (m3)	0.01
IP internal	65

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply




OPTIONAL Pole

FA25133
Pole Ø76 mm h 4500 mm (+500 mm In-ground)



OPTIONAL Pole

FA24933
Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Accessory

F990E00A000
S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Pole

FA24806
Pole Ø76 mm h 3500 mm(with Base)



OPTIONAL Pole

FA414506
Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Bracket

FA22706
Pole Bracket Franco 1/Perseo 3 Ø 60 mm 500 mm Single



OPTIONAL Bracket

FA22133
Pole Bracket Franco 1/Perseo 3 Ø 102 mm 180 mm Single



OPTIONAL Bracket

FA22606
Pole Bracket Franco 1/Perseo 3 Ø 60 mm 180 mm Double



OPTIONAL Accessory

FA116

Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000 mm
with Base



OPTIONAL Bracket

FA22533

Pole Bracket Franco 1/Perseo 3 Ø
60 mm 180 mm Single



OPTIONAL Bracket

FA22233

Pole Bracket Franco 1/Perseo 3 Ø
102 mm 180 mm Double



OPTIONAL Bracket

FA22806

Pole Bracket Franco 1/Perseo 3 Ø
60 mm 500 mm Double



OPTIONAL Bracket

FA22433

Pole Bracket Franco 1/Perseo 3 Ø
102 mm 500 mm Double



OPTIONAL Accessory

FA16630

Antivandal Louvre Perseo 3



OPTIONAL Pole

FA24833

Pole Ø76 mm h 3500 mm (with
Base)



OPTIONAL Pole

FA25006

Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL Pole

FA25033
Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Accessory

FA182
Base Plate and Fixing Bolts Perseo 2



OPTIONAL Bracket

FA22106
Pole Bracket Franco 1/Perseo 3 Ø 102 mm 180 mm Single



OPTIONAL Pole

FA24906
Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Bracket

FA22406
Pole Bracket Franco 1/Perseo 3 Ø 102 mm 500 mm Double



OPTIONAL Bracket

FA23033
Pole Bracket Franco 1/Perseo 3 Ø 76 mm 180 mm Double



OPTIONAL Bracket

FA23233
Pole Bracket Franco 1/Perseo 3 Ø 76 mm 500 mm Double



OPTIONAL Bracket

FA22833
Pole Bracket Franco 1/Perseo 3 Ø 60 mm 500 mm Double



OPTIONAL
Pole

FA415006

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Bracket

FA22506

Pole Bracket Franco 1/Perseo 3 Ø
60 mm 180 mm Single



OPTIONAL
Accessory

FA17930

Pole with base Perseo 3 h 800
mm



OPTIONAL
Bracket

FA23206

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 500 mm Double



OPTIONAL
Bracket

FA23106

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA22206

Pole Bracket Franco 1/Perseo 3 Ø
102 mm 180 mm Double



OPTIONAL
Bracket

FA23006

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 180 mm Double



OPTIONAL
Bracket

FA23133

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA22306

Pole Bracket Franco 1/Perseo 3 Ø
102 mm 500 mm Single



OPTIONAL
Accessory

FA8830

Wall Bracket 620 mm Franco
1/Perseo 3



OPTIONAL
Accessory

FA16530

Wall Washer Visor Perseo 3



OPTIONAL
Pole

FA25106

Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Pole

FA414006

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Bracket

FA22333

Pole Bracket Franco 1/Perseo 3 Ø
102 mm 500 mm Single



OPTIONAL
Pole

FA415033

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Pole

FA415506

Pole Ø 102 mm h 5000 mm (+500
mm In-ground)



OPTIONAL
Bracket

FA22933

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 180 mm Single



OPTIONAL
Accessory

FA18030

Pole Inground Perseo 3 h
2000(+300) mm



OPTIONAL
Bracket

FA22633

Pole Bracket Franco 1/Perseo 3 Ø
60 mm 180 mm Double



OPTIONAL
Bracket

FA22906

Pole Bracket Franco 1/Perseo 3 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA22733

Pole Bracket Franco 1/Perseo 3 Ø
60 mm 500 mm Single



OPTIONAL
Pole

FA414033

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500
mm In-ground)