

# FLOS


FA52516633-310 Anthracite

## Perseo 4 Street Optic Dimmable 1-10V

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON-OFF and dimmable 1-10V or DALI. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<math>\phi</math><math><13\text{mm}</math> cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793648583
Mounting	Wall, Ground
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	53
Source flux (lm)	5859
Lumen Output (lm)	2609

### Physical

Colour	Anthracite
Orientation	Adjustable
Longitudinal tilting (°)	156
Net weight (kg)	5.06
Package height (mm)	155
Package width (mm)	265
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Extreme cut off	No

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



## Accessories & Power Supply



OPTIONAL  
Pole

FA24833

Pole Ø76 mm h 3500 mm(with  
Base)



OPTIONAL  
Accessory

FA990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)



OPTIONAL  
Pole

FA25033

Pole Ø76 mm h 3500 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Double



OPTIONAL  
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Single



OPTIONAL  
Pole

FA24933

Pole Ø76 mm h 4500 mm(with  
Base)



OPTIONAL  
Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL  
Pole

FA25133

Pole Ø76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL Pole

FA414033

Pole Ø 102 mm h 4000 mm With Base



OPTIONAL Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500 mm In-ground)



OPTIONAL Pole

FA415033

Pole Ø 102 mm h 5000 mm With Base



OPTIONAL Accessory

FA116

Base Plate and Fixing Bolts for Pole Ø 102 mm h 4000/5000 mm with Base



OPTIONAL Accessory

FA16730

Wall Washer Visor Perseo 4



OPTIONAL Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Single



OPTIONAL Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Double



OPTIONAL Accessory

FA18133

Wall Bracket Perseo 4 1000 mm



OPTIONAL  
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Double



OPTIONAL  
Bracket

FA9533

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm Double



OPTIONAL  
Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm



OPTIONAL  
Bracket

FA9433

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm



OPTIONAL  
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Single