


## Perseo 4 Street Optic Dimmable Dali

Designed by FLOS Outdoor, 2012



LED source included. Integrated power supply 220-240V ON-OFF and dimmable 1-10V or DALI. Graduated fixing bracket included. Equipped with a M20x1.5 cable guide (for 7mm<ø<13mm cables) and IP68 connector. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use. Optional accessories: protruding arm for walls; feet and arms to install the luminaire on a mast; wall-washer visor and anti-vandalism protection lid. Extraclear transparent glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793644875
Mounting	Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	53
Source flux (lm)	6363
Lumen Output (lm)	2834

### Physical

Colour	Deep Brown
Orientation	Adjustable
Longitudinal tilting (°)	156
Net weight (kg)	5.06
Package height (mm)	155
Package width (mm)	265
Package length (mm)	430
Package volume (m3)	0.02
IP internal	65

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes


Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Pole

FA24806  
Pole Ø76 mm h 3500 mm(with Base)



OPTIONAL Accessory

F990E00A000  
S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Pole

FA24833  
Pole Ø76 mm h 3500 mm(with Base)



OPTIONAL Pole

FA25006  
Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Accessory

FA16730  
Wall Washer Visor Perseo 4



OPTIONAL Bracket

FA8933  
Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Double



OPTIONAL Bracket

FA7933  
Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Single



OPTIONAL Bracket

FA11406  
Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Double



OPTIONAL  
Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm



OPTIONAL  
Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Single



OPTIONAL  
Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Single



OPTIONAL  
Accessory

FA18118

Wall Bracket Perseo 4 1000 mm



OPTIONAL  
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Double



OPTIONAL  
Accessory

FA116

Base Plate and Fixing Bolts for  
Pole Ø 102 mm h 4000/5000 mm  
with Base



OPTIONAL  
Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Single



OPTIONAL  
Bracket

FA9533

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm Double



OPTIONAL  
Pole

FA25033  
Pole Ø76 mm h 3500 mm (+500  
mm In-ground)



OPTIONAL  
Pole

FA24906  
Pole Ø76 mm h 4500 mm(with  
Base)



OPTIONAL  
Pole

FA414533  
Pole Ø 102 mm h 4000 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA11506  
Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Double



OPTIONAL  
Bracket

FA8906  
Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Double



OPTIONAL  
Bracket

FA11306  
Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Single



OPTIONAL  
Bracket

FA9306  
Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm



OPTIONAL  
Bracket

FA9433  
Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm



OPTIONAL  
Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 180 mm Double



OPTIONAL  
Pole

FA414506

Pole Ø 102 mm h 4000 mm (+500  
mm In-ground)



OPTIONAL  
Pole

FA24933

Pole Ø76 mm h 4500 mm(with  
Base)



OPTIONAL  
Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm



OPTIONAL  
Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Double



OPTIONAL  
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø  
76 mm 500 mm Single



OPTIONAL  
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm Double



OPTIONAL  
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 500 mm Double



OPTIONAL  
Pole

FA25106

Pole Ø76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø  
60 mm 180 mm Double



OPTIONAL  
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Single



OPTIONAL  
Pole

FA25133

Pole Ø76 mm h 4500 mm (+500  
mm In-ground)



OPTIONAL  
Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL  
Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 500 mm Single



OPTIONAL  
Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø  
102 mm 180 mm Double