


Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	No

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Accessories & Power Supply



OPTIONAL
Pole

FA414033

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Pole

FA25106

Pole Ø76 mm h 4500 mm (+500
mm In-ground)



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Pole

FA24806

Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Pole

FA24833

Pole Ø76 mm h 3500 mm(with
Base)



OPTIONAL
Accessory

FA18118

Wall Bracket Perseo 4 1000 mm



OPTIONAL
Bracket

FA11533

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Double



OPTIONAL
Pole

FA25006

Pole Ø76 mm h 3500 mm (+500
mm In-ground)



OPTIONAL Pole

FA25033

Pole Ø76 mm h 3500 mm (+500 mm In-ground)



OPTIONAL Pole

FA24906

Pole Ø76 mm h 4500 mm(with Base)



OPTIONAL Bracket

FA7906

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Single



OPTIONAL Bracket

FA9306

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm



OPTIONAL Bracket

FA9406

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 500 mm



OPTIONAL Bracket

FA9533

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm Double



OPTIONAL Bracket

FA11206

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Single



OPTIONAL Bracket

FA8933

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 500 mm Double



OPTIONAL
Bracket

FA9333

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 180 mm



OPTIONAL
Bracket

FA11306

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single



OPTIONAL
Bracket

FA11433

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Double



OPTIONAL
Pole

FA24933

Pole Ø76 mm h 4500 mm(with
Base)



OPTIONAL
Pole

FA414506

Pole Ø 102 mm h 4000 mm (+500
mm In-ground)



OPTIONAL
Accessory

FA16730

Wall Washer Visor Perseo 4



OPTIONAL
Pole

FA415033

Pole Ø 102 mm h 5000 mm With
Base



OPTIONAL
Bracket

FA9433

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm



OPTIONAL Pole

FA25133

Pole Ø76 mm h 4500 mm (+500 mm In-ground)



OPTIONAL Pole

FA415506

Pole Ø 102 mm h 5000 mm (+500 mm In-ground)



OPTIONAL Bracket

FA9506

Pole Bracket Franco 2/Perseo 4 Ø 60 mm 180 mm Double



OPTIONAL Bracket

FA11506

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 500 mm Double



OPTIONAL Bracket

FA9006

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Double



OPTIONAL Pole

FA415006

Pole Ø 102 mm h 5000 mm With Base



OPTIONAL Bracket

FA11406

Pole Bracket Franco 2/Perseo 4 Ø 76 mm 180 mm Double



OPTIONAL Bracket

FA7806

Pole Bracket Franco 2/Perseo 4 Ø 102 mm 180 mm Single



OPTIONAL
Accessory

FA16830

Antivandal Louvre Perseo 4



OPTIONAL
Pole

FA414006

Pole Ø 102 mm h 4000 mm With
Base



OPTIONAL
Bracket

FA7933

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Single



OPTIONAL
Bracket

FA9606

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Accessory

FA116

Base Plate and Fixing Bolts for
Pole Ø 102 mm h 4000/5000 mm
with Base



OPTIONAL
Bracket

FA11233

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 180 mm Single



OPTIONAL
Bracket

FA9633

Pole Bracket Franco 2/Perseo 4 Ø
60 mm 500 mm Double



OPTIONAL
Pole

FA414533

Pole Ø 102 mm h 4000 mm (+500
mm In-ground)



OPTIONAL
Bracket

FA9033

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Double



OPTIONAL
Bracket

FA8906

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 500 mm Double



OPTIONAL
Bracket

FA7833

Pole Bracket Franco 2/Perseo 4 Ø
102 mm 180 mm Single



OPTIONAL
Bracket

FA11333

Pole Bracket Franco 2/Perseo 4 Ø
76 mm 500 mm Single