

Pointbreak Ceiling 1 Optic Spot

Designed by Piero Lissoni




7W - 367lm - 4000K - CRI> 80 - Beam° 11

LED light source included. Integrated 220-240V ON/OFF electrical power. Equipped with double cable gland for inlet and outlet connection.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793406640
Mounting	Ceiling
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	7
System power (W)	6.5
Source flux (lm)	597
Lumen Output (lm)	367

Physical

Colour	Deep Brown
Orientation	Fixed
Net weight (kg)	0.45
Package height (mm)	165
Package width (mm)	170
Package length (mm)	175
Package volume (m3)	0.01
IP internal	65
H2O stop	No
Drive Over	No

Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional