FLOS

F023M43A033 Anthracite

# Pointbreak Ceiling 2 Optic Flood

Designed by Piero Lissoni

18W - 1311lm - 4000K - CRI> 80 - Beam° 50

LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with double cable gland for inlet and outlet connection.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT




## Main specifications

| | |
|---|---|
| EAN | 8054793409962 |
| Mounting | Ceiling |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 18 |
| System power (W) | 17.5 |
| Source flux (lm) | 2030 |
| Lumen Output (lm) | 1311 |

## Physical

| | |
|---|---|
| Colour | Anthracite |
| Orientation | Fixed |
| Net weight (kg) | 1.73 |
| Package height (mm) | 165 |
| Package width (mm) | 270 |
| Package length (mm) | 230 |
| Package volume (m3) | 0.01 |
| IP internal | 65 |
| H2O stop | No |
| Drive Over | No |

## Download

Mounting instructions ZIP

## Photometric Files

LDT / IES ZIP

## Technical Drawings

2D ZIP

3D ZIP

UK CA | RG IEC 62471 | | CE | IP 65 | IK 06



©2026 Flos - P.IVA 00290820174 - 5/26/2026



In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

## Schematic light drawing




Luminous flux luminaire
1311 lm

Beam Angle: 52°

| h(m) | E(lx) | D(m) |
|---|---|---|
| 1 | 1955 | 0.98 |
| 2 | 489 | 1.95 |
| 3 | 217 | 2.93 |
| 4 | 122 | 3.91 |
| 5 | 78 | 4.89 |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **D**




Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

## Photometric

| | |
|---|---|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 50 |
| Beam angle C90-270 (°) | 50 |
| Extreme cut off | No |

## Electrical

| | |
|---|---|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |



©2026 Flos - P.IVA 00290820174 - 5/26/2026


In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.