

Pointbreak Ceiling 2 Optic Spot

Designed by Piero Lissoni




18W - 1149lm - 3000K - CRI> 80 - Beam° 15

LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with double cable gland for inlet and outlet connection.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793408323 |
| Mounting               | Ceiling       |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| Power (W)              | 18            |
| System power (W)       | 17.5          |
| Source flux (lm)       | 1960          |
| Lumen Output (lm)      | 1149          |

### Physical

|                     |            |
|---------------------|------------|
| Colour              | Deep Brown |
| Orientation         | Fixed      |
| Net weight (kg)     | 1.73       |
| Package height (mm) | 165        |
| Package width (mm)  | 270        |
| Package length (mm) | 230        |
| Package volume (m3) | 0.01       |
| IP internal         | 65         |
| H2O stop            | No         |
| Drive Over          | No         |

### Download

Mounting instructions [ZIP](#)

### Photometric Files

LDT / IES [ZIP](#)


### Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 15        |
| Beam angle C90-270 (°) | 15        |
| Extreme cut off        | No        |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Integrated        |
| Dimmable           | Yes               |
| Power supply type  | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |
| Emergency          | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional