

# FLOS

F023G4LA012 Forest Green

## Pointbreak Wall 0 Down Optic Flood

Designed by Piero Lissoni



3W - 108lm - 4000K - CRI> 80 - Beam° 48

LED light source included. Integrated 220-240V ON/OFF electrical power. Equipped with IP65 rubber grommet and 2-pole quick-connect terminals.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793385983 |
| Mounting               | Wall          |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| Power (W)              | 3             |
| System power (W)       | 3.4           |
| Source flux (lm)       | 154           |
| Lumen Output (lm)      | 108           |

### Physical

|                     |              |
|---------------------|--------------|
| Colour              | Forest Green |
| Orientation         | Fixed        |
| Net weight (kg)     | 0.58         |
| Package height (mm) | 80           |
| Package width (mm)  | 135          |
| Package length (mm) | 130          |
| IP internal         | 65           |
| H2O stop            | No           |
| Drive Over          | No           |

### Download

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP


### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



## Schematic light drawing



| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 192   | 0.88 |
| 2    | 48    | 1.76 |
| 3    | 21    | 2.64 |
| 4    | 12    | 3.52 |
| 5    | 8     | 4.40 |

## Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 48        |
| Beam angle C90-270 (°) | 48        |
| Extreme cut off        | No        |

## Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 220-240      |
| Power supply       | Integrated   |
| Dimmable           | No           |
| Power supply type  | Non Dimmable |
| Dimming interface  | Not Dimmable |
| Emergency          | No           |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

