

# FLOS

F023G2EA006 Grey

## Pointbreak Wall 0 Up Optic Spot

Designed by Piero Lissoni




2W - 101lm - 2700K - CRI> 80 - Beam° 11

LED light source included. Integrated 220-240V ON/OFF electrical power. Equipped with IP65 rubber grommet and 2-pole quick-connect terminals.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8054793383279
Mounting	Wall
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	2
System power (W)	2.2
Source flux (lm)	139
Lumen Output (lm)	101

### Physical

Colour	Grey
Orientation	Fixed
Net weight (kg)	0.58
Package height (mm)	80
Package width (mm)	135
Package length (mm)	130
IP internal	65
H2O stop	No
Drive Over	No

### Download

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP


### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



## Schematic light drawing



Beam Angle: 11°

h(m)	E(lx)	D(m)
1	1730	0.19
2	432	0.39
3	192	0.58
4	108	0.78
5	69	0.97

Luminous flux luminaire  
101 lm

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
Extreme cut off	No

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

