

FLOS

F023G4EA001 White

Pointbreak Wall 0 Up Optic Spot

Designed by Piero Lissoni



3W - 108lm - 4000K - CRI> 80 - Beam° 11

LED light source included. Integrated 220-240V ON/OFF electrical power. Equipped with IP65 rubber grommet and 2-pole quick-connect terminals.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------|
| EAN | 8054793385488 |
| Mounting | Wall |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 3 |
| System power (W) | 3.4 |
| Source flux (lm) | 154 |
| Lumen Output (lm) | 108 |

Physical

| | |
|---------------------|-------|
| Colour | White |
| Orientation | Fixed |
| Net weight (kg) | 0.58 |
| Package height (mm) | 80 |
| Package width (mm) | 135 |
| Package length (mm) | 130 |
| IP internal | 65 |
| H2O stop | No |
| Drive Over | No |

Download

[Mounting instructions](#) ZIP

Photometric Files

[LDT / IES](#) ZIP


Technical Drawings

[2D](#) ZIP

[3D](#) ZIP



Schematic light drawing



Beam Angle: 11°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 1850 | 0.19 |
| 2 | 462 | 0.39 |
| 3 | 206 | 0.58 |
| 4 | 116 | 0.78 |
| 5 | 74 | 0.97 |

Luminous flux luminaire
108 lm

Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 4000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 11 |
| Beam angle C90-270 (°) | 11 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

