

## Pointbreak Wall 2 Up&Down Optic Medium

Designed by Piero Lissoni




32W - 2610lm - 4000K - CRI> 80 - Beam° 26

LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with double cable gland for inlet and outlet connection. Upwards, single emission version, available upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793402192 |
| Mounting               | Wall          |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | Power LED     |
| Number of lamps        | 1             |
| Power (W)              | 32            |
| System power (W)       | 32            |
| Source flux (lm)       | 4060          |
| Lumen Output (lm)      | 2610          |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | Black |
| Orientation         | Fixed |
| Net weight (kg)     | 5.61  |
| Package height (mm) | 165   |
| Package width (mm)  | 380   |
| Package length (mm) | 230   |
| Package volume (m3) | 0.15  |
| IP internal         | 65    |
| H2O stop            | No    |
| Drive Over          | No    |

### Download

Mounting instructions [↓ ZIP](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

|                                 |                  |
|---------------------------------|------------------|
| Lighting type                   | Direct, Indirect |
| Light distribution              | Symmetric        |
| CCT (K)                         | 4000             |
| CRI>                            | 80               |
| Beam angle C0-180 (°)           | 26               |
| Beam angle C90-270 (°)          | 26               |
| Beam angle indirect C0-180 (°)  | 26               |
| Beam angle indirect C90-270 (°) | 26               |
| Extreme cut off                 | No               |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Integrated        |
| Dimmable           | Yes               |
| Power supply type  | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |
| Emergency          | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional