

Pointbreak Wall 2 Up&Down Optic Spot

Designed by Piero Lissoni



32W - 2380lm - 4000K - CRI> 80 - Beam° 15

LED light source included. Integrated 220-240V ON/OFF and 1-10V/DALI dimmable electrical power. Equipped with double cable gland for inlet and outlet connection. Upwards, single emission version, available upon request.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793401881
Mounting	Wall
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	32
System power (W)	32
Source flux (lm)	4060
Lumen Output (lm)	2380

Physical

Colour	Deep Brown
Orientation	Fixed
Net weight (kg)	5.61
Package height (mm)	165
Package width (mm)	380
Package length (mm)	230
Package volume (m3)	0.15
IP internal	65
H2O stop	No
Drive Over	No

Download

Mounting instructions [↓ ZIP](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct, Indirect
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
Beam angle indirect C0-180 (°)	15
Beam angle indirect C90-270 (°)	15
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional