

FLOS


F6394031 Anthracite

Skynest Motion

Designed by Marcel Wanders, Marcel Wanders studio, 2022

57W - 1325lm - 2700-2900K - CRI> 90

Diffuse lighting hanging appliance. The dome is a combination of luminous and dark elements arranged into a network and formed of core structures covered with a thin interwoven colourful tubular mesh made from recycled and recyclable fabric produced from polyester. Every single luminous element is powered by special micro-connectors located at the top of the dome and is covered with a two-tone mesh, while the side facing the inside of the dome is always white in order to allow for optimal light emission from the LED module. The appliance is fitted with a built-in balancing system at the top of the dome which helps adjust its balance, making it perfectly stable. The bottom of the dome is completed by an aluminium ring that keeps the dome's entire network structure in place through a simple snap-fit system. The product is assembled with absolutely no glue so it can be fully separated to be recycled in the future and in case of any repairs or replacements. Available lamp finishes: Blue Tourmaline, Almond, Anthracite or Brick Red. Plastic structure painted with the same finish as the lamp, fitted with built-in electronics and dimmer.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8059607057216
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	57
System power (W)	57
System flux (lm)	1325

Physical

Color	Anthracite
Length (in)	90.55
Cord color	Black
Canopy color	Black
Canopy height (in)	0.984
Net weight (lb)	13.23
Gross weight (lb)	40.79
Package volume (in)	20039.3
IP internal	20

Download

Mounting instructions



PDF

Photometric Files

LDT / IES



ZIP

Technical Drawings

2D



ZIP


3D



ZIP




Schematic light drawing



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700-2900
CRI>	90
Extreme cut off	No


Electrical

Insulation class	III
Main voltage (Vac)	100-240
Driver	Integrated
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Dimmer Integrated
Plug type	Type A, Type C, Type G

Spare Parts




- | | | |
|-----|--|-----------|
| 01. | Skynest Motion – Black ceiling rose and steel cable assembly | RF6391031 |
| 02. | Assembly Led Arm for Skynest Suspension Black | RF34720 |
| 04. | Skynest Motion Black emc dimmer assembly | RF37552 |
| 05. | Black plug assembly kit & 48V driver | RF6600130 |



RF6391031
Skynest Motion – Black ceiling
rose and steel cable assembly



RF34720
Assembly Led Arm for Skynest
Suspension Black



RF37552
Skynest Motion Black emc
dimmer assembly



RF6600130
Black plug assembly kit & 48V
driver