

Smithfield Ceiling Pro

Designed by Jasper Morrison, 2009



45W - 2732lm - 3000K - CRI> 95

Ceiling-mounted lamp emitting direct light. Features an aluminium body with an injection-moulded opalescent methacrylate diffuser. Steel ceiling and wall attachment. LED module integrated available in 2700K and 3000K colour temperatures; 3500K available upon request. Dimmable through Dali or Push control options.

Part of the Smithfield family by Jasper Morrison, Smithfield Ceiling draws inspiration from the industrial lighting of London's historic Smithfield Market. True to Morrison's Super Normal design philosophy, it balances utilitarian character with refined simplicity. The ceiling-mounted version retains the generous form of the suspension lamp in a clean, space-conscious solution. With its combination of technical performance and understated presence, Smithfield Ceiling is equally suited to both domestic and commercial environments.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607039861
Mounting	Ceiling
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2732

Physical

Color	Red
Length (in)	23.62
Net weight (lb)	12.79
Gross weight (lb)	21.39
Package height (in)	12.2
Package width (in)	27.95
Package length (in)	27.95
Package volume (in)	9536.22
IP internal	20

Download

Mounting instructions



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



REPLACEABLE2



PWRSUPRPL2



IP
20

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	95
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Notes

Dimmable 0-10V (10% up to 100% for 120V and 25% up to 100% for 277V).

3500K customised product. Please consult the Sales Department for delivery times.

Class 2



Spare Parts

