

FLOS


FU136631 Matte Black



Smithfield Ceiling Pro

Designed by Jasper Morrison, 2009

Smithfield Ceiling LED version is available in two color temperatures 2700K and 3000K. Available in 3500K, please inquiry for more details. Part of the Smithfield family, the Smithfield ceiling mounted dimmable lamp manages to be both grand and unassuming in halogen and LED versions. Providing direct light through its aluminum body, it is well suited for a variety of environments. Available in glossy black, matte black, mud, and white. Its diffuser is injection-molded opalescent PC (polycarbonate). The wall and ceiling attachment is steel. Inspiration behind the design: English designer Jasper Morrison is known for his ability to take the beauty that he sees in the world around him and translate it into his work. To that end, the Smithfield family was named for the Smithfield Market in London, where the artist was inspired by the industrial nature of the fixtures he saw. "I've always liked the industrial and functional character of these lights," he says. "I wanted to make a project out of them, looking for some way of making use of their efficiency in delivering light, and the forms themselves which are so much a part of the good atmosphere of industrial spaces."



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607010600
Mounting	Ceiling
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2623

Physical

Color	Matte Black
Length (in)	23.62
Net weight (lb)	12.79
Gross weight (lb)	21.39
Package height (in)	27.95
Package width (in)	12.2
Package length (in)	27.95
Package volume (in)	9536.22
IP internal	20

Download

Family spec sheet




Mounting instructions



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F





Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Batteries inside No

Notes

Dimmable 0-10V (10% up to 100% for 120V and 25% up to 100% for 277V).
3500K customised product. Please consult the Sales Department for delivery times.
Class 2

FLOS

01.	Smithfield C/S Pro Power supply	RF38640
	1050 mA	
02.	Methacrylate diffuser	RF19022

FLOS

RF38640

Smithfield C/S Pro Power supply
1050 mA



RF19022

Methacrylate diffuser