

FLOS

FS003202 Glossy Black

Smithfield Suspension Pro

Designed by Jasper Morrison, 2009



45W - 2732lm - 3000K - CRI> 95

Suspension lamp emitting direct light. Features an aluminium body with an injection-moulded opalescent methacrylate diffuser. Steel ceiling attachment and suspension cable. Equipped with a five-pole power cable in PTFE with double insulation. LED module integrated available in 2700K and 3000K colour temperatures; 3500K available upon request. Dimmable through Dali or Push control options.

Designed by Jasper Morrison, Smithfield Suspension is inspired by the industrial fittings of London's historic Smithfield Market. True to Morrison's Super Normal design philosophy, it translates utilitarian charm into refined simplicity. The lamp's generous form provides ample direct light while remaining discreet in appearance. Known for creating objects that quietly enhance everyday spaces, Morrison balances functional performance with understated presence with a lamp equally suited to both domestic and commercial settings.

Download

Mounting instructions



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



REPLACEABLE2



PWRSUPRPL2

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8059607010402
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2732

Physical

Color	Glossy Black
Length (in)	23.62
Cord length (in)	106.299
Canopy height (in)	1.417
Net weight (lb)	12.79
Gross weight (lb)	21.39
Package height (in)	12.2
Package width (in)	27.95
Package length (in)	27.95
Package volume (in)	9536.22
IP internal	20



IP
20

Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	3000
CRI>	95
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Notes

Dimmable 0-10V (10% up to 100% for 120V and 25% up to 100% for 277V).

3500K customised product. Please consult the Sales Department for delivery times.

Steel cable 13.12ft.

Class 2

Spare Parts

