

# FLOS


FU136730 Glossy Black

## Smithfield Suspension Pro

Designed by Jasper Morrison, 2009



Smithfield Suspension LED version is now available in two color temperatures 2700K and 3000K. Available in 3500K, please inquiry for more details. Part of the Smithfield family, the Smithfield Suspension manages to be both grand and unassuming in Halogen and new LED versions. Providing direct light through its aluminum body, it is well suited for a variety of environments. Available in black, matte black, mud and white. Its diffuser is injection-molded opalescent PC (polycarbonate). The steel ceiling attachment features a steel suspension cable, and the three-pole electric cable is PTFE double insulation. Inspiration behind the design: Jasper Morrison is known for his ability to take the beauty that he sees in the world around him and translate it into his work. To that end, the Smithfield family was named for the Smithfield Market in London, where the artist was inspired by the industrial nature of the fixtures he saw. "I've always liked the industrial and functional character of these lights," he says. "I wanted to make a project out of them, looking for some way of making use of their efficiency in delivering light, and the forms themselves which are so much a part of the good atmosphere of industrial spaces."



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)


### Download

Family spec sheet [ZIP](#)

Mounting instructions [PDF](#)

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by a professional

## Main specifications

EAN	8059607010655
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	45
System power (W)	45
System flux (lm)	2623

## Physical

Color	Glossy Black
Length (in)	23.62
Cord color	Clear
Canopy color	Black
Canopy height (in)	1.417
Net weight (lb)	12.79
Gross weight (lb)	21.39
Package height (in)	27.95
Package width (in)	12.2
Package length (in)	27.95
Package volume (in)	9536.22
IP internal	20



## Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No


## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Notes

Dimmable 0-10V (10% up to 100% for 120V and 25% up to 100% for 277V).  
 3500K customised product. Please consult the Sales Department for delivery times.  
 Steel cable 13.12ft.  
 Class 2

## Spare Parts



01.	Black ceiling rose assembly	RAU369230
02.	Kit of 5 or rings	RF05382
03.	Power Cord for Smithfield	RF19342
04.	4mt steel wire Ø1,2 with 19 winded wires	RF01089
04.	3 mt steel cable ø1,2 with 19 winded wires	RF29665
05.	Smithfield C/S Pro Power supply 1050 mA	RF38640
06.	Methacrylate diffuser	RF19022



RAU369230

Black ceiling rose assembly



RF05382

Kit of 5 or rings



RF19342

Power Cord for Smithfield




RF01089

4mt steel wire Ø1,2 with 19  
winded wires



RF29665

3 mt steel cable ø1,2 with 19  
winded wires



RF38640

Smithfield C/S Pro Power supply  
1050 mA



RF19022

Methacrylate diffuser