

Soft Spun LED Small

Designed by Sebastian Wrong, 2010




LED - Top LED - 28W - 1184lm - 3000K - CRI> 90

Recessed luminaire for LED lamp. Non-dimmable 220/240V power supply included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	28
System power (W)	35
Lumen Output (lm)	1184

Physical

Colour	Raw
Trim	No
Orientation	Fixed
Recessed depth (mm)	35
Length (mm)	590
Net weight (kg)	11
IP internal	20
IP external	20

Download

Mounting instructions



Ecodesign and Energy Labelling



Non-replaceable light source



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Extreme cut off	No

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	240
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable
Dimming interface	Not Dimmable
Emergency	No