

# FLOS

F025A3BAU18 Deep Brown


## Spine 1 Absolute

Designed by Vincent Van Duysen, 2021



982lm - 3000K - CRI> 80 - Beam° 15

LED COB light source included. Integrated electric power supply ON/OFF. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793418902
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
System power (W)	11
Source flux (lm)	1325
System flux (lm)	982

### Physical

Color	Deep Brown
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Cord length (in)	196.850
Net weight (lb)	2.2
Package height (in)	4.72
Package width (in)	4.72
Package length (in)	12.2
Package volume (in)	272.41
IP internal	66
IP external	66

### Download

[Family spec sheet](#) ZIP

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings

[2D](#) ZIP

[3D](#) ZIP


### Ecodesign and Energy

#### Labelling

This product contains a light source of energy efficiency class E



## Schematic light drawing



h(m)	E(lx)	D(m)
1	9267	0.25
2	2317	0.49
3	1030	0.74
4	579	0.98
5	371	1.23

### Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
Extreme cut off	No

### Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	110-127
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable

## Accessories & Power Supply



OPTIONAL  
Accessory

F025Z060000

Honeycomb Louvre



OPTIONAL  
Accessory

F026Z010000

Ground Spike