

# FLOS

■ F026A4CBU30.A Black

## Spine 2 Absolute Dimmable 1-10V

Designed by Vincent Van Duysen, 2021



4000K - CRI> 80

LED COB light source included. Integrated electric power supply ON/OFF and adjustable 1-10 V or DALI. Fixing plate included. The electrical connection is made on the inside of the plate by means of a watertight connector included. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Ground spike for ground installations to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793795164        |
| Mounting               | Ground               |
| Environments           | Outdoor wet location |
| Light Source Type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| System power (W)       | 19.5                 |
| Source flux (lm)       | 0                    |

### Physical

|                     |        |
|---------------------|--------|
| Color               | Black  |
| Net weight (lb)     | 3.97   |
| Gross weight (lb)   | 4.41   |
| Package height (in) | 4.72   |
| Package width (in)  | 12.2   |
| Package length (in) | 4.72   |
| Package volume (in) | 272.41 |

### Download

Mounting instructions [↓ ZIP](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)

### Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Schematic light drawing



Photometric

|                    |           |
|--------------------|-----------|
| Lighting type      | Direct    |
| Light distribution | Symmetric |
| CCT (K)            | 4000      |
| CRI>               | 80        |
| Extreme cut off    | No        |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 110-127           |
| Driver             | Integrated        |
| Dimmable           | Yes               |
| Dimming type       | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |