

Designed by Vincent Van Duysen, 2021



The technical drawings show two probe configurations:

- Standard Probe:** Features a cylindrical body with a total length of 175 mm and a maximum width of 193 mm at the top. The contact tip has a diameter of Ø35 mm. Below the main body is a smaller section with a diameter of Ø20 mm.
- Probe with Large Diameter Contact Tip:** Features a similar cylindrical body with a total length of 108 mm and a maximum width of Ø90 mm. The contact tip is significantly larger than the standard one.

BOOK AN APPOINTMENT


EAN	8054793495859
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	17
Source flux (lm)	1739
Lumen Output (lm)	1302

Colour	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	270
Net weight (kg)	2.5
Package height (mm)	205
Package width (mm)	290
Package length (mm)	265
Package volume (m3)	0.02
IP internal	66

Mounting instructions ZIP

LDT / IES ZIP2D ZIP3D  ZIP

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	36

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable 1-10V
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply



REQUIRED
Accessory

F026Z020001

Rod Ø20 mm h 200 mm



REQUIRED
Accessory

F026Z030001

Rod Ø20 mm h 500 mm



OPTIONAL
Accessory

F990C030000

4 way junction box 5 poles IP68
(6-14 mm cables)



OPTIONAL
Accessory

F990C080000

Connector kit 5-pole flying socket
+ EU plug IP68.



OPTIONAL
Accessory

F990C110000

Gelbox IPX8 for splicing
connectors



OPTIONAL
Accessory

F026Z060000

Honeycomb Louvre



OPTIONAL
Accessory

F029Z020000

Converter Spine 2 Optic Medium
Flood



OPTIONAL
Accessory

F029Z021000

Converter Spine 2 Optic Flood



OPTIONAL
Accessory
F029Z022000
Converter Spine 2 Optic Wide
Flood



OPTIONAL
Accessory
F029Z023000
Converter Spine 2 Optic Elliptic 1



OPTIONAL
Accessory
F029Z024000
Converter Spine 2 Optic Elliptic 2



OPTIONAL
Accessory
F029Z025000
Converter Spine 2 Optic Wall



OPTIONAL
Accessory
F026Z050001
Visor