


F026V3FB001 White

## Spine L 2 Pro Elliptical 1 Dimmable 1-10V

Designed by Vincent Van Duysen, 2021



Power LED source included. Equipped with an integrated snoot for higher visual comfort. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF and adjustable 1-10 V or DALI. Minimum L-shaped mounting support integrated. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                       |
|------------------------|-----------------------|
| EAN                    | 8054793522203         |
| Mounting               | Ceiling, Wall, Ground |
| Environments           | Outdoor wet location  |
| Light source type      | LED                   |
| Light sources included | Yes                   |
| LED type               | Power LED             |
| Number of lamps        | 1                     |
| System power (W)       | 10.5                  |
| Source flux (lm)       | 966                   |
| Lumen Output (lm)      | 744                   |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | White      |
| Orientation              | Adjustable |
| Longitudinal tilting (°) | 155        |
| Net weight (kg)          | 2.5        |
| Package height (mm)      | 205        |
| Package width (mm)       | 290        |
| Package length (mm)      | 265        |
| Package volume (m3)      | 0.02       |
| IP internal              | 66         |

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |
| CCT (K)            | 3000       |
| CRI>               | 80         |

Electrical

|                    |                   |
|--------------------|-------------------|
| Insulation class   | I                 |
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Power supply       | Integrated        |
| Dimmable           | Yes               |
| Power supply type  | Dimmable 1-10V    |
| Dimming interface  | Dimmer Integrated |
| Emergency          | No                |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply




OPTIONAL  
Accessory

F990C030000  
4 way junction box 5 poles IP68  
(6-14 mm cables)



OPTIONAL  
Accessory

F990C080000  
Connector kit 5-pole flying socket  
+ EU plug IP68.



OPTIONAL  
Accessory

F990C110000  
Gelbox IPX8 for splicing  
connectors



OPTIONAL  
Accessory

F026Z060000  
Honeycomb Louvre



OPTIONAL  
Accessory

F029Z020000  
Converter Spine 2 Optic Medium  
Flood



OPTIONAL  
Accessory

F029Z021000  
Converter Spine 2 Optic Flood



OPTIONAL  
Accessory

F029Z022000  
Converter Spine 2 Optic Wide  
Flood



OPTIONAL  
Accessory

F029Z023000  
Converter Spine 2 Optic Elliptic 1



OPTIONAL  
Accessory

F029Z024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL  
Accessory

F029Z025000

Converter Spine 2 Optic Wall