

■ F026V4HD030 Black

Designed by Vincent Van Duysen, 2021

[illegible]

BOOK AN APPOINTMENT

EAN	8054793524108
Mounting	Ceiling, Wall, Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	10.5
Source flux (lm)	1012
Lumen Output (lm)	722

Colour	Black
Orientation	Adjustable
Longitudinal tilting (°)	155
Net weight (kg)	2.5
Package height (mm)	205
Package width (mm)	290
Package length (mm)	265
Package volume (m3)	0.02
IP internal	66

Mounting instructions ZIP

LDT / IES ZIP2D ZIP3D ZIP

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	80

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALI 1
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Notes

5 m neoprene cable (10 m upon request) for remote connection.

Accessories & Power Supply




OPTIONAL
Accessory
F990C030000
4 way junction box 5 poles IP68
(6-14 mm cables)



OPTIONAL
Accessory
F990C080000
Connector kit 5-pole flying socket
+ EU plug IP68.



OPTIONAL
Accessory
F026Z060000
Honeycomb Louvre



OPTIONAL
Accessory
F990C110000
Gelbox IPX8 for splicing
connectors



OPTIONAL
Accessory
F029Z020000
Converter Spine 2 Optic Medium
Flood



OPTIONAL
Accessory
F029Z021000
Converter Spine 2 Optic Flood



OPTIONAL
Accessory
F029Z022000
Converter Spine 2 Optic Wide
Flood



OPTIONAL
Accessory
F029Z023000
Converter Spine 2 Optic Elliptic 1



OPTIONAL
Accessory

F029Z024000

Converter Spine 2 Optic Elliptic 2



OPTIONAL
Accessory

F029Z025000

Converter Spine 2 Optic Wall