

FLOS

03.6285.40CDA White

Spot 120 Dali Version


Designed by FLOS Architectural, 2016



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	14
System power (W)	14.5
Source flux (lm)	1003
Lumen Output (lm)	746
Efficacy (lm/W)	51

Physical

Colour	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Transversal tilting (°)	90
Length (mm)	46
Net weight (kg)	0.35
Package height (mm)	19
Package width (mm)	22
Package length (mm)	17
IP internal	20

Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings

[2D](#) ZIP

[3D](#) ZIP


[Bim](#) ZIP



Ecodesign and Energy Labelling



Schematic light drawing



h(m)	E(lx)	D(m)
1	7301	0.28
2	1825	0.57
3	811	0.85
4	456	1.14
5	292	1.42

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Rf fidelity index	90
Rg gamut index	99
LED Life / Failure Ratio	L80B20 >36.000h (Tc=85°C)
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	18
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions.