

FLOS

03.6287.14CDD Black

Spot 120 Dali Version


Designed by FLOS Architectural, 2016



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	14
System power (W)	14.5
Source flux (lm)	1002
System flux (lm)	493

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Transversal tilting (°)	90
Length (in)	1.81
Net weight (lb)	0.78
Package height (in)	0.75
Package width (in)	0.87
Package length (in)	0.67
Package volume (in)	428
IP internal	20

Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Rf fidelity index	91
Rg gamut index	98
LED Life / Failure Ratio	L80B20 >36.000h (Tc=85°C)
Beam angle C0-180 (°)	31
Beam angle C90-270 (°)	31
Extreme cut off	No
UGR _L	<10

Electrical

Forward voltage (V)	24
LED current (mA)	900
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	10-100
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Maximum 11 spots for a single driver. Accessories included (honeycomb and screening crosspiece). For wireless lighting control, choose integrated Casambi versions. Class 2.