

FLOS

03.8072.05BDA Polished Aluminium

Spot 150 Dali Version

Designed by FLOS Architectural, 2017



Accent lighting LED module.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	22.5
System power (W)	24.1
Source flux (lm)	2411
System flux (lm)	1818
Efficacy (lm/W)	90.45

Physical

Color	Polished Aluminium
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (in)	7.01
Net weight (lb)	0.93
IP internal	20



*installed in The Tracking Magnet

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings


2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	21
Beam angle C90-270 (°)	21
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	470
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming range (%)	10-100
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Only compatible with DALI profile version.

Accessories & Power Supply



OPTIONAL
Accessory
Optical

08.0526.00


Snoot shielding cone



OPTIONAL
Accessory
Optical

08.8428.00

Honeycomb



OPTIONAL
Accessory
Optical

08.8429.00

Screening crosspiece



OPTIONAL
Accessory
Optical

08.8431.00

Elliptical lens



OPTIONAL
Accessory
Optical

08.8432.00

Flood lens



OPTIONAL
Accessory
Optical

08.0526.40

Snoot shielding cone