

## Spot Non Dimmable

Designed by FLOS Architectural, 2020



LED - Power LED - 6W - 340lm - 2700K - CRI> 90 - Beam° 13

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic current converter. On/Off version, non-dimmable.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

| Mounting               | Track               |
|------------------------|---------------------|
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 6                   |
| System power (W)       | 6                   |
| Source flux (lm)       | 545                 |
| Lumen Output (lm)      | 340                 |
| Efficacy (lm/W)        | 56.67               |

### Physical

| Colour                   | White      |
|--------------------------|------------|
| Orientation              | Adjustable |
| Rotation (°)             | 267        |
| Longitudinal tilting (°) | 90         |
| Spot diameter (mm)       | 35         |
| Length (mm)              | 41         |
| Net weight (kg)          | 0.07       |
| IP internal              | 20         |

### Download

Mounting instructions



### Photometric Files

LDT / IES



### Technical Drawings

2D



3D



 Bim




### Ecodesign and Energy Labelling



REPLACEABLE2



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 2         |
| Beam angle C0-180 (°)  | 13        |
| Beam angle C90-270 (°) | 13        |
| UGRL                   | <10       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Insulation class    | III                                   |
| Forward voltage (V) | 24                                    |
| Power supply        | Remote excluded                       |
| Dimmable            | Yes                                   |
| Power supply type   | Non Dimmable, Dimmable                |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Accessories & Power Supply



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.0191.14

Honeycomb for Spot