

FLOS

03.2236.14A Black

Spot Non Dimmable

Designed by FLOS Architectural, 2020



LED - Power LED - 6W - 301lm - 3000K - CRI> 90 - Beam° 20

LED accent lighting module for installation in the The Micro Running Magnet Pro system. Integrated DC/DC electronic current converter. On/Off version, non-dimmable.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	6
System power (W)	6
Source flux (lm)	585
System flux (lm)	301
Efficacy (lm/W)	50.17

Physical

Color	Black
Orientation	Adjustable
Rotation (°)	267
Longitudinal tilting (°)	90
Length (in)	1.62
Net weight (lb)	0.16
Gross weight (lb)	0.29
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files

LDT / IES	ZIP
-----------	-----


Technical Drawings

2D	ZIP
3D	ZIP

Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20
UGRL	<10

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)