

Super Line Down


Designed by FLOS Architectural



Efficient and delicate luminaire featuring a high technological level. It is composed of a bar combining direct and indirect light and held by two transparent unipolar cables that provide support and electrical wiring. Perfect for offices or places that require high lighting efficiency and comfort. Collection of uspended luminaries for general lighting with a signature minimalist shape, designed to offer high-performance lighting, light quality and visual comfort combined in a very compact size.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	38.6
System power (W)	39
Source flux (lm)	4609
System flux (lm)	3571
Efficacy (lm/W)	91.56

Physical

Color	Brushed Brass
Orientation	Fixed
IP internal	20
IP external	20

Download


Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50 - 50.0000h (Tc 85°C)
Beam angle C0-180 (°)	76
Beam angle C90-270 (°)	82
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	35.9
LED current (mA)	1050
Driver	Remote
Dimmable	Yes
Dimming type	Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Cable 5 m

Accessories & Power Supply



REQUIRED
Accessory

08.0524.40.19

Super Line Suspension Kit
accessory for Remote installation,
White



REQUIRED
Accessory

08.0524.14.19

Super Line Suspension Kit
accessory for Remote installation,
Black



REQUIRED
Accessory

08.0524.02.19

Super Line Suspension Kit
accessory for Remote installation,
Grey



REQUIRED
Accessory

Installation

08.0524.ET.19

Remote Suspension KIT




REQUIRED
Accessory

Installation

08.0524.EU.19

Remote Suspension KIT



REQUIRED
Power supply

Electrical

SP40W1050MA-10V-A02

Remote Splice Box 9.5"x2.5"x1.5",
1050mA , 40W, 0-10V Dimmable,
120V/277V