

03.8142.14A90 Black

Suspension Panel 600 Rod 100 mm On Board Dimmer


24.5W - 1647lm - 3000K - CRI> 90 - Beam° 113



Suspended luminaire with rigid rod, to be installed in the Infra-Structure system.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Power (W)	24.5
System power (W)	25.6
Source flux (lm)	3540
System flux (lm)	1647

Physical

Color	Black
Orientation	Fixed
Length (in)	1
Net weight (lb)	10.94
Gross weight (lb)	17.25
Package volume (in)	7628
IP internal	20

Download


Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	113
Beam angle C90-270 (°)	113

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	850
Driver	Remote