

# FLOS

05.4593.ES.CB Brushed Bronze

## The Glowing Track 360 Surface Casambi + Wall PSU

Designed by FLOS Architectural, 2025



Length: 1210 - Surface

360° surface ambient lighting system that provides uniform light distribution. Available in 1200 mm. Driver not included. Driver and plug included. Supplied with three plug types: EU, UK and USA.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	24.8
System power (W)	27.6
Source flux (lm)	2968
Lumen Output (lm)	2130

### Physical

Colour	Brushed Bronze
Orientation	Fixed
Length (mm)	1210
Cord length (mm)	2500
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

2D [↓ ZIP](#)


3D [↓ ZIP](#)



### Ecodesign and Energy Labelling



## Schematic light drawing



### Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	92
Rg gamut index	89
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
UGR <sub>L</sub>	<19

### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No