

# FLOS

05.4695.ES.DA Brushed Bronze

## The Glowing Track 360 Surface Remote Driver Dali

Designed by FLOS Architectural, 2025




Length: 610 - Surface

360° surface ambient lighting system that provides uniform light distribution. Available in four lengths (600 mm, 1200 mm, 1800 mm, and 2400 mm). Driver not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	12.4
System power (W)	13.8
Source flux (lm)	1232
Lumen Output (lm)	884

### Physical

Colour	Brushed Bronze
Orientation	Fixed
Length (mm)	610
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



### Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2200
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B10>72.000h_Tc65°C
Extreme cut off	No

### Electrical

Insulation class	III
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.0615.00

Ceiling fixing kit



REQUIRED  
Power supply

Electrical

60.9705A

Remote Power Supply Non  
Dimmable 24V. 60W. 220/240V



OPTIONAL  
Connector

08.1205.ES

Linear Joint Surface



OPTIONAL  
Connector

08.1206.ES

Corner Joint 2  
Suspension/Surface



OPTIONAL  
Connector

08.1207.ES

Corner Joint 3  
Suspension/Surface



OPTIONAL  
Connector

08.1208.ES

Corner Joint 4  
Suspension/Surface